

WCS, WALL-MOUNTED WC, TOILETS, SIPHONIC TOILETS, RIMLESS TOILETS, WALL-MOUNTED TOILETS ARCHITECTURA

PRODUCT INFORMATION

1 . POSITION



Model	4688UR
Width	22 7/8" inch
Depth	16 1/8" inch
Weight	52,91 lbs
Description	<p>DirectFlush washdown model, elongated design Sanitary porcelain this product works with industry standard in-wall carrier/tank systems such as those manufactured by Viega, Geberit and TOTO. Please refer to their respective compatibility charts. EN 997 This wall-mounted toilet is made of vitreous china. The wall-mounted toilet is 22 7/8" (580mm) x 16 1/8" (410mm). The product has a concealed trapway and a D-shape bowl. The product is with ceramic plus. The product has a water use of 1.6/0.8. gpf (6/3 lpf). The wall- mounted toilet is Villeroy & Boch model 4688UR. ADA compliant, EPA - Watersense, meets and exceeds ASME A112.19.2/CSA B45.1 ASME A112.19.14, Certifications: IAPMO(cUPC), State of Massachusetts, Code Compliance: UPC, IPC, NSPC, NPC Canada and others washdown model concealed trapway D-shape bowl one year limited warranty minimum Water pressure: 8 psi water surface: 4" x 5" (100 x 130 mm) trap diameter: 2 3/8" (60 mm) trap seal: 2 1/4" (55mm) minimum rough-in: 7" (180 mm) rough-in rear outlet</p>
Water use	0,79 / 1,59 gal
Installation	wall-mounted
Outlet	concealed trapway
Material	Sanitary porcelain
Leed	4

Specification texts

; Elongated wall-mounted directflush toilet; DirectFlush; Sanitary porcelain; Size: 22 7/8" x 16 1/8" (580 x 410 mm); Oval; washdown model, elongated design; wall-mounted; this product works with industry standard in-wall carrier/tank systems such as those manufactured by Viega, Geberit and TOTO. Please refer to their respective compatibility charts.; Water use: 0,79 / 1,59 gal; Leed: 4; EN 997; concealed trapway; This wall-mounted toilet is made of vitreous china. The wall-mounted toilet is 22 7/8" (580mm) x 16 1/8" (410mm). The product has a concealed trapway and a D-shape bowl. The product is with ceramic plus. The product has a water use of 1.6/0.8. gpf (6/3 lpf). The wall-mounted toilet is Villeroy & Boch model 4688UR.; ADA compliant, EPA - Watersense, meets and exceeds ASME A112.19.2/CSA B45.1 ASME A112.19.14, Certifications: IAPMO(cUPC), State of Massachusetts, Code Compliance: UPC, IPC, NSPC, NPC Canada and others; washdown model; concealed trapway; D-shape bowl; one year limited warranty; minimum Water pressure: 8 psi; water surface: 4" x 5" (100 x 130 mm); trap diameter: 2 3/8" (60 mm); trap seal: 2 1/4" (55mm); minimum rough-in: 7" (180 mm) rough-in; rear outlet

COLOURS

White	4688UR01	4051202568771
Alpin		

TECHNICAL DRAWINGS

4688UR

