

WCS, WALL-MOUNTED WC, TOILETS, SIPHONIC TOILETS, WALL-MOUNTED TOILETS LA BELLE

PRODUCT INFORMATION

1 . POSITION



Model	5627U1
Width	15 1/8" inch
Height	23" inch
Depth	23" inch
Weight	70,55 lbs
Description	<p>washdown model Sanitary porcelain this product works with industry standard in-wall carrier/tank systems such as those manufactured by Viega, Geberit and TOTO. Please refer to their respective compatibility charts. includes "Supra-Fix" mounting system This wall-mounted toilet is made of vitreous china. The wall-mounted toilet is 23" (585mm) x 15 1/8" (385mm). The product has a concealed trapway and a D-shape bowl. The product is with ceramic plus. The product has a water use of 1.6/0.8. gpf (6/3 lpf). The wall-mounted toilet is Villeroy & Boch model 5627U1. meets and exceeds ASME A112.19.2/CSA B45.1 ASME A112.19.14, Certifications: IAPMO(cUPC), EPA Watersense, City of Los Angeles and others, Code Compliance: UPC, IPC, NSPC, NPC Canada and others, EPA - Watersense washdown model concealed trapway D-shape bowl one year limited warranty minimum Water pressure: 8 psi water surface: 4" x 5" (100 x 130 mm) trap diameter: 2 1/8" (51mm) trap seal: 2 1/4" (57mm) minimum rough-in: 7" (180 mm) rough-in rear outlet</p>
Water use	0,79 / 1,59 gal
Installation	wall-mounted
Outlet	concealed trapway
Material	Sanitary porcelain
Leed	2

Specification texts

; Washdown toilet; Sanitary porcelain; Size: 15 1/8" x 23" x 23" (385 x 585 x 585 mm); washdown model; wall-mounted; this product works with industry standard in-wall carrier/tank systems such as those manufactured by Viega, Geberit and TOTO. Please refer to their respective compatibility charts.; Water use: 0,79 / 1,59 gal; Leed: 2; includes "Supra-Fix" mounting system; concealed trapway; This wall-mounted toilet is made of vitreous china. The wall-mounted toilet is 23" (585mm) x 15 1/8" (385mm). The product has a concealed trapway and a D-shape bowl. The product is with ceramic plus. The product has a water use of 1.6/0.8. gpf (6/3 lpf). The wall-mounted toilet is Villeroy & Boch model 5627U1.; meets and exceeds ASME A112.19.2/CSA B45.1 ASME A112.19.14, Certifications: IAPMO(cUPC), EPA Watersense, City of Los Angeles and others, Code Compliance: UPC, IPC, NSPC, NPC Canada and others, EPA - Watersense; washdown model; concealed trapway; D-shape bowl; one year limited warranty; minimum Water pressure: 8 psi; water surface: 4" x 5" (100 x 130 mm); trap diameter: 2 1/8" (51mm); trap seal: 2 1/4" (57mm); minimum rough-in: 7" (180 mm) rough-in; rear outlet

COLOURS

White Alpin CeramicPlus	5627U1R1	4051202166250
----------------------------	----------	---------------

TECHNICAL DRAWINGS

5627U1

