

# WCS, FLOOR-STANDING WC, TOILETS, 2PC-SIPHONIC, FLOOR-MOUNTED TOILETS ARCHITECTURA

## PRODUCT INFORMATION

### 1 . POSITION



Model	5645U1
Width	14 3/8" inch
Depth	28 3/4" inch
Weight	91,73 lbs
Description	<p>siphonic jet model, elongated design, A.D.A. height Sanitary porcelain 12" rough-in</p> <p>This two-piece toilet is made of vitreous china. The two-piece toilet is 28 3/4" (730mm) x 14 3/8" (365mm) x 32 1/2" (825mm). The product has an concealed trapway and an elongated bowl. The two-piece toilet is Villeroy &amp; Boch model 5645U1. It is available as 1.28 gpf single flush (bowl 5645U1 + tank 7757U1) or 1.28/0.93 gpf dual flush (bowl 5645U1 + tank 7757V1). meets and exceeds ASME A112.19.2/CSA B45.1 ASME A112.19.14, Certifications: IAPMO(cUPC), EPA Watersense, City of Los Angeles and others, Certifications: IAPMO(cUPC), State of Massachusetts, ADA compliant (only with tank 7757 U1)</p> <p>siphonic jet model concealed trapway elongated bowl one year limited warranty minimum Water pressure: 8 psi water surface: 8 1/2" x 9 1/2" (214 x 240 mm) trap diameter: 2 1/4" (58 mm) trap seal: 2 1/2" (63mm) minimum rough-in: 12" (305 mm) rough-in bottom outlet trip lever chrome finish</p>
Water use	0,79 / 1,19 gal
Installation	floor-standing
Outlet	concealed trapway with fixation covers
Material	Sanitary porcelain
Lead	4

## Specification texts

; Siphonic toilet; Sanitary porcelain;  
Size: 14 3/8" x 28 3/4" (365 x 730 mm); Oval; siphonic jet model, elongated design, A.D.A. height; floor-standing; 12" rough-in; Water use: 0,79 / 1,19 gal; Leed: 4; concealed trapway with fixation covers; This two-piece toilet is made of vitreous china. The two-piece toilet is 28 3/4" (730mm) x 14 3/8" (365mm) x 32 1/2" (825mm). The product has an concealed trapway and an elongated bowl. The two-piece toilet is Villeroy & Boch model 5645U1. It is available as 1.28 gpf single flush (bowl 5645U1 + tank 7757U1) or 1.28/0.93 gpf dual flush (bowl 5645U1 + tank 7757V1).; meets and exceeds ASME A112.19.2/CSA B45.1 ASME A112.19.14, Certifications: IAPMO(cUPC), EPA Watersense, City of Los Angeles and others, Certifications: IAPMO(cUPC), State of Massachusetts, ADA compliant (only with tank 7757 U1); siphonic jet model; concealed trapway; elongated bowl; one year limited warranty; minimum Water pressure: 8 psi; water surface: 8 1/2" x 9 1/2" (214 x 240 mm); trap diameter: 2 1/4" (58 mm); trap seal: 2 1/2" (63mm); minimum rough-in: 12" (305 mm) rough-in; trip lever chrome finish; bottom outlet

## COLOURS

White Alpin    5645U101    4051202572211

# TECHNICAL DRAWINGS

## 5645U1

