

WCS, FLOOR-STANDING WC, TOILETS, 1PC-SIPHONIC, FLOOR-MOUNTED  
TOILETS STRADA

---

PRODUCT INFORMATION

---

1 . POSITION



Model	5650US
Width	14 3/8" inch
Depth	28 3/4" inch
Weight	114,64 lbs
Description	<p>Sanitary porcelain                      12" rough-in                      incl. SoftClosing WC seat 9M04 S1 01                      composed of: Consisting of:                      Siphonic WC, rough in 12" from the wall, <b>Tank</b>, bottom inlet, flushing mechanism with chrome trip lever, WC-seat and cover with QuickRelease and SoftClosing hinges 9M30 U1 01, incl. fastening set</p> <p>This one-piece toilet is made of vitreous china. The one-piece toilet is 28 3/4" (730mm) x 14 3/8" (365mm) x 28 7/8" (735mm). The product has a concealed trapway and an elongated bowl. The product has a water use of 1.28 gpf (4.8 lpf). The one-piece toilet is Villeroy &amp; Boch model 5650US                      Certifications: IAPMO(cUPC), EPA Watersense, City of Los Angeles and others, Certifications: IAPMO(cUPC), State of Massachusetts, ADA compliant, meets and exceeds ASME A112.19.2/CSA B45.1 ASME A112.19.14                      siphonic jet model                      concealed trapway                      elongated bowl                      one year limited warranty                      minimum Water pressure: 8 psi                      minimum rough-in: 12" (305 mm)                      rough-in                      bottom outlet</p>
Installation	floor-standing
Outlet	concealed trapway
Material	Sanitary porcelain
Lead	4

---

Specification texts

; One-piece toilet; Sanitary porcelain; Size: 14 3/8" x 28 3/4" (365 x 730 mm); Oval; floor-standing; 12" rough-in; Leed: 4; incl. SoftClosing WC seat 9M04 S1 01; concealed trapway; This one-piece toilet is made of vitreous china. The one-piece toilet is 28 3/4" (730mm) x 14 3/8" (365mm) x 28 7/8" (735mm). The product has a concealed trapway and an elongated bowl. The product has a water use of 1.28 gpf (4.8 lpf). The one-piece toilet is Villeroy & Boch model 5650US; Certifications: IAPMO(cUPC), EPA Watersense, City of Los Angeles and others, Certifications: IAPMO(cUPC), State of Massachusetts, ADA compliant, meets and exceeds ASME A112.19.2/CSA B45.1 ASME A112.19.14; siphonic jet model; concealed trapway; elongated bowl; one year limited warranty; minimum Water pressure: 8 psi; minimum rough-in: 12" (305 mm) rough-in; bottom outlet

---

## COLOURS

White	5650US01	4051202558994
Alpin		

# TECHNICAL DRAWINGS

## 5650US

