

# WCS, FLOOR-STANDING WC, TOILETS, 2PC-SIPHONIC, FLOOR-MOUNTED TOILETS STRADA

## PRODUCT INFORMATION

### 1 . POSITION



Model	5655U0
Width	14 3/8" inch
Depth	28 3/4" inch
Weight	92,11 lbs
Description	<p>siphonic jet model, elongated design, A.D.A. height Sanitary porcelain 12" rough-in</p> <p>This two-piece toilet is made of vitreous china. The two-piece toilet is 28 3/4" (730mm) x 14 3/8" (365mm) x 31 7/8" (810mm). The product has an concealed trapway and an elongated bowl. The product has a water use of 1.28 gpf (4.8 lpf). The two-piece toilet is Villeroy &amp; Boch model 5655U0</p> <p>Certifications: IAPMO(cUPC), EPA Watersense, City of Los Angeles and others, Certifications: IAPMO(cUPC), State of Massachusetts, ADA compliant, meets and exceeds ASME A112.19.2/CSA B45.1 ASME A112.19.14</p> <p>siphonic jet model concealed trapway elongated bowl one year limited warranty minimum Water pressure: 8 psi water surface: 6" x 8 5/8" (152 x 219 mm) trap diameter: 2 1/4" (58 mm) trap seal: 2 1/4" (58 mm) minimum rough-in: 12" (305 mm) rough-in bottom outlet</p>
Installation	floor-standing
Outlet	concealed trapway with fixation covers
Material	Sanitary porcelain
Lead	4

---

Specification texts

; Siphonic toilet; Sanitary porcelain;  
Size: 14 3/8" x 28 3/4" (365 x 730 mm); Oval; siphonic jet model, elongated design, A.D.A. height; floor-standing; 12" rough-in; Leed: 4; concealed trapway with fixation covers; This two-piece toilet is made of vitreous china. The two-piece toilet is 28 3/4" (730mm) x 14 3/8" (365mm) x 31 7/8" (810mm). The product has an concealed trapway and an elongated bowl. The product has a water use of 1.28 gpf (4.8 lpf). The two-piece toilet is Villeroy & Boch model 5655U0; Certifications: IAPMO(cUPC), EPA Watersense, City of Los Angeles and others, Certifications: IAPMO(cUPC), State of Massachusetts, ADA compliant, meets and exceeds ASME A112.19.2/CSA B45.1 ASME A112.19.14; siphonic jet model; concealed trapway; elongated bowl; one year limited warranty; minimum Water pressure: 8 psi; water surface: 6" x 8 5/8" (152 x 219 mm); trap diameter: 2 1/4" (58 mm); trap seal: 2 1/4" (58 mm); minimum rough-in: 12" (305 mm) rough-in; bottom outlet

---

## COLOURS

White	5655U001	4051202491024
Alpin		

# TECHNICAL DRAWINGS

## 5655U0

