

WCS, FLOOR-STANDING WC, TOILETS, 2PC-SIPHONIC, FLOOR-MOUNTED TOILETS O.NOVO

PRODUCT INFORMATION

1 . POSITION



Model	5659U0
Width	15 1/8" inch
Height	32 5/8" inch
Depth	27 3/8" inch
Weight	57,1 lbs
Description	<p>siphonic jet model, round front design, A.D.A. height Sanitary porcelain 12" rough-in This two-piece toilet is made of vitreous china. The two-piece toilet is 27 3/8" (695mm) x 15 1/8" (385mm) x 32 5/8" (830mm). The product has an open trapway and an round-front bowl. The product has a water use of 1.28 gpf (4.8 lpf). The two-piece toilet is Villeroy & Boch model 5659U0 Certifications: IAPMO(cUPC), EPA Watersense, City of Los Angeles and others, Certifications: IAPMO(cUPC), State of Massachusetts, ADA compliant, meets and exceeds ASME A112.19.2/CSA B45.1 ASME A112.19.14 siphonic jet model open trapway round-front bowl one year limited warranty minimum Water pressure: 8 psi water surface: 7 3/8" x 9 1/4" (186 x 233 mm) trap diameter: 2 1/4" (58 mm) trap seal: 2 3/8" (60mm) minimum rough-in: 12" (305 mm) rough-in bottom outlet trip lever chrome finish</p>
Water use	0,79 / 1,19 gal
Installation	floor-standing
Outlet	open trapway
Material	Sanitary porcelain
Lead	4

Specification texts

; Siphonic toilet; Sanitary porcelain;
Size: 15 1/8" x 32 5/8" x 27 3/8" (385 x 830 x 695 mm); Oval; siphonic jet model, round front design, A.D.A. height; floor-standing; 12" rough-in; Water use: 0,79 / 1,19 gal; Leed: 4; open trapway; This two-piece toilet is made of vitreous china. The two-piece toilet is 27 3/8" (695mm) x 15 1/8" (385mm) x 32 5/8" (830mm). The product has an open trapway and a round-front bowl. The product has a water use of 1.28 gpf (4.8 lpf). The two-piece toilet is Villeroy & Boch model 5659U0; Certifications: IAPMO(cUPC), EPA Watersense, City of Los Angeles and others, Certifications: IAPMO(cUPC), State of Massachusetts, ADA compliant, meets and exceeds ASME A112.19.2/CSA B45.1 ASME A112.19.14; siphonic jet model; open trapway; round-front bowl; one year limited warranty; minimum Water pressure: 8 psi; water surface: 7 3/8" x 9 1/4" (186 x 233 mm); trap diameter: 2 1/4" (58 mm); trap seal: 2 3/8" (60mm); minimum rough-in: 12" (305 mm) rough-in; trip lever chrome finish; bottom outlet

COLOURS

White	5659U001	4051202347505
Alpin		

TECHNICAL DRAWINGS

5659U0

