

WCS, FLOOR-STANDING WC, TOILETS, 1PC-SIPHONIC, FLOOR-MOUNTED TOILETS ARCHITECTURA

PRODUCT INFORMATION

1 . POSITION



Model	5697US
Width	14 3/8" inch
Depth	28 1/2" inch
Weight	102,74 lbs
Description	<p>Overall dimensions: (L) 28 1/2" x (W) 14 3/8" x (H) 29" siphonic jet model, skirted, elongated design, A.D.A. height, incl. WC seat 9M30 U1 01 Sanitary porcelain 12" rough-in</p> <p>composed of: Consisting of: Siphonic WC, rough in 12" from the wall, Tank, bottom inlet, flushing mechanism with chrome trip lever, WC-seat and cover with QuickRelease and SoftClosing hinges 9M30 U1 01, incl. fastening set, incl. WC seat 9150 U1 01</p> <p>This one-piece toilet is made of vitreous china. The one-piece toilet is 28 1/2" (725mm) x 14 3/8" (365mm) x 28 1/2" (725mm). The product has a concealed trapway and an elongated bowl. The product has a water use of 1.28 gpf (4.8 lpf). The one-piece toilet is Villeroy & Boch model 5697US</p> <p>Certifications: IAPMO(cUPC), EPA Watersense, City of Los Angeles and others, ADA compliant, meets and exceeds ASME A112.19.2/CSA B45.1 ASME A112.19.14, EPA - Watersense</p> <p>siphonic jet model concealed trapway elongated bowl one year limited warranty minimum Water pressure: 8 psi minimum rough-in: 12" (305 mm) rough-in bottom outlet trip lever chrome finish</p>
Water use	1,28 / 0 gal
Installation	floor-standing
Outlet	concealed trapway with fixation covers
Material	Sanitary porcelain

Specification texts

; One-piece toilet; Overall dimensions: (L) 28 1/2" x (W) 14 3/8" x (H) 29"; Sanitary porcelain; Size: 14 3/8" x 28 1/2" (365 x 725 mm); Oval; siphonic jet model, skirted, elongated design, A.D.A. height, incl. WC seat 9M30 U1 01; floor-standing; 12" rough-in; Water use: 1,28 / 0 gal; concealed trapway with fixation covers; This one-piece toilet is made of vitreous china. The one-piece toilet is 28 1/2" (725mm) x 14 3/8" (365mm) x 28 1/2" (725mm). The product has a concealed trapway and an elongated bowl. The product has a water use of 1.28 gpf (4.8 lpf). The one-piece toilet is Villeroy & Boch model 5697US; Certifications: IAPMO(cUPC), EPA Watersense, City of Los Angeles and others, ADA compliant, meets and exceeds ASME A112.19.2/CSA B45.1 ASME A112.19.14, EPA - Watersense; siphonic jet model; concealed trapway; elongated bowl; one year limited warranty; minimum Water pressure: 8 psi; minimum rough-in: 12" (305 mm) rough-in; trip lever chrome finish; bottom outlet

COLOURS

White Alpin 5697US01 4051202354404

TECHNICAL DRAWINGS

5697US

