

WCS, FLOOR-STANDING WC, TOILETS, SIPHONIC TOILETS, FLOOR-MOUNTED TOILETS SUBWAY

PRODUCT INFORMATION

1 . POSITION



Model	6607U1
Width	14 5/8" inch
Depth	22" inch
Weight	69,45 lbs
Description	<p>washdown model Sanitary porcelain we recommend installation with 3 7/8" distance to the wall, this product works with industry standard in-wall carrier/tank systems such as those manufactured by Viega, Geberit and TOTO. Please refer to their respective compatibility charts. Incl. fastening set for concealed mounting system EN 997 designed for rear outlet This floor-standing toilet is made of vitreous china. The floor-standing toilet is 22 1/2" (570mm) x 14 5/8" (370mm). The product has a concealed trapway and a D-shape bowl. The product is with ceramic plus. The product has a water use of 1.6/0.8. gpf (6/3 lpf). The 0 is Villeroy & Boch model 6607U1. Certifications: IAPMO(cUPC), City of Los Angeles and others, Code Compliance: UPC, IPC, NSPC, NPC Canada and others, meets and exceeds ASME A112.19.2/CSA B45.1 ASME A112.19.14 washdown model concealed trapway D-shape bowl one year limited warranty minimum Water pressure: 8 psi water surface: 4" x 5 1/4" (100 x 133 mm) trap diameter: 2 1/8" (51mm) trap seal: 2 1/4" (50mm) minimum rough-in: 7" (180 mm) rough-in rear outlet</p>
Water use	0,79 / 1,59 gal
Installation	floor-standing, close to the wall
Outlet	concealed trapway
Material	Sanitary porcelain
Leed	2

Specification texts

; Floor-standing toilet with inwall tank; Sanitary porcelain; Size: 14 5/8" x 22" (370 x 560 mm); Oval; washdown model; floor-standing, close to the wall; we recommend installation with 3 7/8" distance to the wall, this product works with industry standard in-wall carrier/tank systems such as those manufactured by Viega, Geberit and TOTO. Please refer to their respective compatibility charts.; Water use: 0,79 / 1,59 gal; Leed: 2; Incl. fastening set for concealed mounting system; EN 997; concealed trapway; designed for rear outlet; This floor-standing toilet is made of vitreous china. The floor-standing toilet is 22 1/2" (570mm) x 14 5/8" (370mm). The product has a concealed trapway and a D-shape bowl. The product is with ceramic plus. The product has a water use of 1.6/0.8. gpf (6/3 lpf). The 0 is Villeroy & Boch model 6607U1.; Certifications: IAPMO(cUPC), City of Los Angeles and others, Code Compliance: UPC, IPC, NSPC, NPC Canada and others, meets and exceeds ASME A112.19.2/CSA B45.1 ASME A112.19.14; washdown model; concealed trapway; D-shape bowl; one year limited warranty; minimum Water pressure: 8 psi; water surface: 4" x 5 1/4" (100 x 133 mm); trap diameter: 2 1/8" (51mm); trap seal: 2 1/4" (50mm); minimum rough-in: 7" (180 mm) rough-in; rear outlet

COLOURS

White Alpin	6607U101	4051202165079
White Alpin CeramicPlus	6607U1R1	4051202165062

TECHNICAL DRAWINGS

6607U1

