

BATHROOM FURNITURE, MIRROR, MIRRORS/MIRROR CABINETS, MIRROR MEDICINE CABINETS, MIRROR CABINETS, MIRRORS WITH ELECTRIC PLUGS, MIRRORS WITH LIGHTING PERCEPTION

PRODUCT INFORMATION

1 . POSITION




Model	B418U0
Width	39 3/8" inch
Height	29 3/8" inch
Depth	6 1/8" inch
Weight	58,18 lbs
Description	<p>Glass fastening set included integral LED lighting Equipped with: 2 mirrored doors, 4 adjustable glass shelves, 1 magnifying mirror, 1 magnetic strip, electric outlet and switch, factory installed mirrored side panels UL listed soft closing hinges fully assembled 4 x wood screw cylinder head KS 1/4" / 2 3/8" (5.5/60 mm), 4 x UNI-dowel polyamide F3/8" x 1 5/8" (F8 x 40 mm), 1 x pouch 3 15/16" x 9 3/8" (100x250 mm), 2 x mounting rail 4 15/16" (125 mm)</p>
Material	Glass
Specification texts	<p>; +; Semi-built-in medicine cabinet; Glass; Size: 39 3/8" x 29 3/8" x 6 1/8" (1001 x 747 x 157 mm); fastening set included; integral LED lighting; Equipped with: 2 mirrored doors, 4 adjustable glass shelves, 1 magnifying mirror, 1 magnetic strip, electric outlet and switch, factory installed mirrored side panels; UL listed; soft closing hinges; fully assembled; 4 x wood screw cylinder head KS 1/4" / 2 3/8" (5.5/60 mm), 4 x UNI-dowel polyamide F3/8" x 1 5/8" (F8 x 40 mm), 1 x pouch 3 15/16" x 9 3/8" (100x250 mm), 2 x mounting rail 4 15/16" (125 mm)</p>


COLOURS

B418U000 4051202378554

TECHNICAL DRAWINGS

B418U0

 110 - 120 V mains connection, loose
 The product is designed for connection through an UL listed metal conduit with nominal trade size of 1/2".
 The product shall be supplied through an UL listed cord rated minimum 300 V, 3 x 14 AWG, 60°C / 140°F and solid copper conductor only.

 Wall mounting

* Dimensions taken from finished floor level

