

WCS, WALL-MOUNTED WC, TOILETS, WALL-MOUNTED SUBWAY

PRODUCT INFORMATION

1 . POSITION



Model	5600U0
Width	14 3/4" inch
Depth	22 1/4" inch
Weight	56,33 lbs
Description	<p>washdown model Sanitary porcelain In-wall tank/carrier can be ordered from Toto (WT152M DUOFIT IN-WALL TANK SYSTEM) or Geberit (article # 111.335.00.5) includes "Supra-Fix" mounting system This wall-mounted toilet is made of vitreous china. The wall-mounted toilet is 22 1/4" (565mm) x 14 3/4" (375mm). The product has a concealed trapway and a D-shape bowl. The product is with ceramic plus. The product has a water use of 1.6/0.8. gpf (6/3 lpf). The wall-mounted toilet is Villeroy & Boch model 5600U0. meets and exceeds ASME A112.19.2/CSA B45.1 ASME A112.19.14, Certifications: IAPMO(cUPC), EPA Watersense, City of Los Angeles and others, Code Compliance: UPC, IPC, NSPC, NPC Canada and others, EPA - Watersense washdown model concealed trapway D-shape bowl one year limited warranty minimum Water pressure: 8 psi water surface: 4" x 5 1/5" (104 x 132 mm) trap diameter: 2 1/8" (51mm) trap seal: 2 1/4" (55mm) minimum rough-in: 7" (180 mm) rough-in rear outlet</p>
Water use	0,79 / 1,59 gal
Outlet	concealed trapway
Material	Sanitary porcelain
Leed	2

Specification texts

; Wall-mounted toilet - sleek; Sanitary porcelain; Size: 14 3/4" x 22 1/4" (375 x 565 mm); washdown model; In-wall tank/carrier can be ordered from Toto (WT152M DUOFIT IN-WALL TANK SYSTEM) or Geberit (article # 111.335.00.5); Water use: 0,79 / 1,59 gal; Leed: 2; includes "Supra-Fix" mounting system; concealed trapway; This wall-mounted toilet is made of vitreous china. The wall-mounted toilet is 22 1/4" (565mm) x 14 3/4" (375mm). The product has a concealed trapway and a D-shape bowl. The product is with ceramic plus. The product has a water use of 1.6/0.8. gpf (6/3 lpf). The wall-mounted toilet is Villeroy & Boch model 5600U0.; meets and exceeds ASME A112.19.2/CSA B45.1 ASME A112.19.14, Certifications: IAPMO(cUPC), EPA Watersense, City of Los Angeles and others, Code Compliance: UPC, IPC, NSPC, NPC Canada and others, EPA - Watersense; washdown model; concealed trapway; D-shape bowl; one year limited warranty; minimum Water pressure: 8 psi; water surface: 4" x 5 1/5" (104 x 132 mm); trap diameter: 2 1/8" (51mm); trap seal: 2 1/4" (55mm); minimum rough-in: 7" (180 mm) rough-in; rear outlet

COLOURS

White Alpin	5600U001	4051202166274
White Alpin CeramicPlus	5600U0R1	4051202166267

TECHNICAL DRAWINGS

5600U0

