

# WCS, WALL-MOUNTED WC, TOILETS, WALL-MOUNTED SUBWAY

## PRODUCT INFORMATION

### 1 . POSITION



|             |   |
|-------------|---|
| Model       | 5614UR  |
| Width       | 14 5/8" inch  |
| Depth       | 22" inch  |
| Weight      | 55,56 lbs   |
| Description | <p>DirectFlush<br/>washdown model<br/>Sanitary porcelain<br/>In-wall tank/carrier can be ordered from Toto (WT152M DUOFIT IN-WALL TANK SYSTEM) or Geberit (article # 111.335.00.5) incl. "Supra-Fix 3.0" mounting system</p> <p>This wall-mounted toilet is made of vitreous china. The wall-mounted toilet is 22" (560mm) x 14 5/8" (370mm). The product has a concealed trapway and a D-shape bowl. The product is with ceramic plus. The product has a water use of 1.6/0.8. gpf (6/3 lpf). The wall-mounted toilet is Villeroy &amp; Boch model 5614UR</p> <p>ADA compliant, EPA - Watersense, meets and exceeds ASME A112.19.2/CSA B45.1 ASME A112.19.14, Certifications: IAPMO(cUPC), EPA Watersense, City of Los Angeles and others, Certifications: IAPMO(cUPC), State of Massachusetts, Code Compliance: UPC, IPC, NSPC, NPC Canada and others</p> <p>washdown model<br/>concealed trapway<br/>D-shape bowl<br/>one year limited warranty<br/>minimum Water pressure: 8 psi<br/>water surface: 4" x 5" (100 x 130 mm)<br/>trap diameter: 2" (50mm)<br/>trap seal: 2 3/8" (60mm)<br/>minimum rough-in: 7" (180 mm)<br/>rough-in<br/>rear outlet</p> |
| Water use   | 0,79 / 1,19 gal   |
| Outlet      | concealed trapway   |
| Material    | Sanitary porcelain  |
| Leed        | 4   |

Specification texts

; Wall-mounted toilet with rimless flushing (Directflush); DirectFlush; Sanitary porcelain; Size: 14 5/8" x 22" (370 x 560 mm); washdown model; In-wall tank/carrier can be ordered from Toto (WT152M DUOFIT IN-WALL TANK SYSTEM) or Geberit (article # 111.335.00.5); Water use: 0,79 / 1,19 gal; Leed: 4; incl. "Supra-Fix 3.0" mounting system; concealed trapway; This wall-mounted toilet is made of vitreous china. The wall-mounted toilet is 22" (560mm) x 14 5/8" (370mm). The product has a concealed trapway and a D-shape bowl. The product is with ceramic plus. The product has a water use of 1.6/0.8. gpf (6/3 lpf). The wall-mounted toilet is Villeroy & Boch model 5614UR; ADA compliant, EPA - Watersense, meets and exceeds ASME A112.19.2/CSA B45.1 ASME A112.19.14, Certifications: IAPMO(cUPC), EPA Watersense, City of Los Angeles and others, Certifications: IAPMO(cUPC), State of Massachusetts, Code Compliance: UPC, IPC, NSPC, NPC Canada and others; washdown model; concealed trapway; D-shape bowl; one year limited warranty; minimum Water pressure: 8 psi; water surface: 4" x 5" (100 x 130 mm); trap diameter: 2" (50mm); trap seal: 2 3/8" (60mm); minimum rough-in: 7" (180 mm) rough-in; rear outlet

COLOURS

|                         |          |               |
|-------------------------|----------|---------------|
| White Alpin             | 5614UR01 | 4051202373092 |
| White Alpin CeramicPlus | 5614URR1 | 4051202373108 |

TECHNICAL DRAWINGS

5614UR

