

WCS, FLOOR-STANDING WC, TOILETS, 2PC-SIPHONIC ARCHITECTURA

PRODUCT INFORMATION

1 . POSITION



Model	5646U1
Width	14 3/8" inch
Depth	25 1/4" inch
Weight	83,75 lbs
Description	<p>siphonic jet model, round front design, A.D.A. height Sanitary porcelain 12" rough-in This two-piece toilet is made of vitreous china. The two-piece toilet is 25 1/4" (640mm) x 14 3/8" (365mm) x 32 1/2" (825mm). The product has a concealed trapway and an round-front bowl. The product has a water use of 1.28 gpf (4.8 lpf). The two-piece toilet is Villeroy & Boch model 5646U1 meets and exceeds ASME A112.19.2/CSA B45.1 ASME A112.19.14, Certifications: IAPMO(cUPC), EPA Watersense, City of Los Angeles and others, Certifications: IAPMO(cUPC), State of Massachusetts, ADA compliant siphonic jet model concealed trapway round-front bowl one year limited warranty minimum Water pressure: 8 psi water surface: 8 1/2" x 9 1/2" (214 x 240 mm) trap seal: 2 1/2" (63mm) minimum rough-in: 12" (305 mm) rough-in bottom outlet</p>
Water use	1,28 / 1,28 gal
Installation	Floor-standing
Outlet	concealed trapway with fixation covers
Material	Sanitary porcelain
Lead	2

Specification texts

; 2-PC-Toilet bowl; Sanitary porcelain; Size: 14 3/8" x 25 1/4" (365 x 640 mm); siphonic jet model, round front design, A.D.A. height; Floor-standing; 12" rough-in; Water use: 1,28 / 1,28 gal; Leed: 2; concealed trapway with fixation covers; This two-piece toilet is made of vitreous china. The two-piece toilet is 25 1/4" (640mm) x 14 3/8" (365mm) x 32 1/2" (825mm). The product has a concealed trapway and an round-front bowl. The product has a water use of 1.28 gpf (4.8 lpf). The two-piece toilet is Villeroy & Boch model 5646U1; meets and exceeds ASME A112.19.2/CSA B45.1 ASME A112.19.14, Certifications: IAPMO(cUPC), EPA Watersense, City of Los Angeles and others, Certifications: IAPMO(cUPC), State of Massachusetts, ADA compliant; siphonic jet model; concealed trapway; round-front bowl; one year limited warranty; minimum Water pressure: 8 psi; water surface: 8 1/2" x 9 1/2" (214 x 240 mm); trap seal: 2 1/2" (63mm); minimum rough-in: 12" (305 mm) rough-in; bottom outlet

COLOURS

White	5646U101	4051202572235
Alpin		

TECHNICAL DRAWINGS

5646U1

