

WCS, FLOOR-STANDING WC, TOILETS, 1PC-SIPHONIC O.NOVO

PRODUCT INFORMATION

1 . POSITION



Model	5668US
Width	14 3/8" inch
Depth	28 3/8" inch
Weight	84,88 lbs
Description	<p>siphonic jet model, elongated design, A.D.A. height Sanitary porcelain 12" rough-in composed of: Consisting of: Siphonic WC, Outlet support 12" from the wall, Tank, bottom inlet, flushing mechanism with chrome push-button, WC-seat and cover with QuickRelease and SoftClosing hinges 9M30 U1 01, Fastening set This one-piece toilet is made of vitreous china. The one-piece toilet is 28 3/8" (720mm) x 14 3/8" (365mm) x 27 1/2" (700mm). The product has an open trapway and an elongated bowl. The product has a water use of 1.28 gpf (4.8 lpf). The one-piece toilet is Villeroy & Boch model 5668US. Certifications: IAPMO(cUPC), EPA Watersense, City of Los Angeles and others, Certifications: IAPMO(cUPC), State of Massachusetts, ADA compliant, meets and exceeds ASME A112.19.2/CSA B45.1 ASME A112.19.14 siphonic jet model open trapway elongated bowl one year limited warranty minimum Water pressure: 8 psi water surface: 7 7/8" x 9 1/3" (198 x 237mm) trap diameter: 2 1/4" (58 mm) trap seal: 2 3/8" (60mm) minimum rough-in: 12" (305 mm) rough-in bottom outlet trip lever chrome finish</p>
Water use	1,28 / 1,28 gal
Installation	Floor-standing
Outlet	open trapway
Material	Sanitary porcelain
Leed	2

Specification texts

; 1-PC toilet; Sanitary porcelain;
Size: 14 3/8" x 28 3/8" (365 x 720 mm); siphonic jet model, elongated design, A.D.A. height; Floor-standing; 12" rough-in; Water use: 1,28 / 1,28 gal; Leed: 2; open trapway; This one-piece toilet is made of vitreous china. The one-piece toilet is 28 3/8" (720mm) x 14 3/8" (365mm) x 27 1/2" (700mm). The product has an open trapway and an elongated bowl. The product has a water use of 1.28 gpf (4.8 lpf). The one-piece toilet is Villeroy & Boch model 5668US.;
Certifications: IAPMO(cUPC), EPA Watersense, City of Los Angeles and others, Certifications: IAPMO(cUPC), State of Massachusetts, ADA compliant, meets and exceeds ASME A112.19.2/CSA B45.1 ASME A112.19.14; siphonic jet model; open trapway; elongated bowl; one year limited warranty; minimum Water pressure: 8 psi; water surface: 7 7/8" x 9 1/3" (198 x 237mm); trap diameter: 2 1/4" (58 mm); trap seal: 2 3/8" (60mm); minimum rough-in: 12" (305 mm) rough-in; trip lever chrome finish; bottom outlet

COLOURS

White	5668US01	4051202382988
Alpin		

TECHNICAL DRAWINGS

5668US

